

# TLS 0022 & Minor Production Torque Screwdrivers

## Torque range from 0.005 to 1.35 N.m

Compact tamperproof tools that deliver the correct torque accurately and repeatedly



Order now... call our Sales Hotline +44 (0) 1483 894 476

Order Code	Model	Range		Drive	k mm	g	Repeatability	ISO 6789 Class	Colour
		ISO	Imperial						
015000	TLS 0022 Micro FH	2-22 cN.m	3-32 ozf.in		76	050	+/- 6%	2F	Red
015080	TLS 0022 FH	0.5-22 cN.m	0.7-32 ozf.in		104	072	+/- 6%	2F	Gold
015085	TLS 0022 FH O/W	0.5-22 cN.m	0.7-32 ozf.in		116	085	+/- 6%	2F	Gold
015100	Minor SD	2-135 cN.m	0.18-12 lbf.in		143	210	+/- 6%	2F	Blue
015105	Minor SD O/W	2-135 cN.m	0.18-12 lbf.in		143	210	+/- 6%	2F	Blue
015200	Minor FH	2-135 cN.m	0.18-12 lbf.in		111	210	+/- 6%	2F	Blue
015205	Minor FH O/W	2-135 cN.m	0.18-12 lbf.in		125	210	+/- 6%	2F	Blue
015120	Minor SD	2-135 cN.m	0.18-12 lbf.in		143	210	+/- 6%	2F	Green
015125	Minor SD O/W	2-135 cN.m	0.18-12 lbf.in		143	210	+/- 6%	2F	Green
015220	Minor FH	2-135 cN.m	0.18-12 lbf.in		111	210	+/- 6%	2F	Green
015225	Minor FH O/W	2-135 cN.m	0.18-12 lbf.in		125	210	+/- 6%	2F	Green
015140	Minor SD	2-135 cN.m	0.18-12 lbf.in		143	210	+/- 6%	2F	Red
015145	Minor SD O/W	2-135 cN.m	0.18-12 lbf.in		143	210	+/- 6%	2F	Red
015240	Minor FH	2-135 cN.m	0.18-12 lbf.in		111	210	+/- 6%	2F	Red
015245	Minor FH O/W	2-135 cN.m	0.18-12 lbf.in		125	210	+/- 6%	2F	Red
015160	Minor SD	2-135 cN.m	0.18-12 lbf.in		143	210	+/- 6%	2F	Gold
015165	Minor SD O/W	2-135 cN.m	0.18-12 lbf.in		143	210	+/- 6%	2F	Gold
015260	Minor FH	2-135 cN.m	0.18-12 lbf.in		111	210	+/- 6%	2F	Gold
015265	Minor FH O/W	2-135 cN.m	0.18-12 lbf.in		125	210	+/- 6%	2F	Gold



Torqueleader sell a comprehensive range of Accessories, Bits & Blades for **TLS Screwdrivers**...see page 66 or visit [www.torqueleader.com](http://www.torqueleader.com) for details

# TLS Standard Production Torque Screwdrivers

## Torque range from 0.06 to 4.06 N.m

Compact tamperproof tools that deliver the correct torque accurately and repeatedly



Order now... call our Sales Hotline +44 (0) 1483 894 476

Order Code	Model	Range		Drive	k mm	g	Repeatability	ISO 6789 Class	Colour
		ISO	Imperial						
015500	Standard SD	6-406 cN.m	0.5-36 lbf.in		159	280	+/- 6%	2F	Blue
015505	Standard SD O/W	6-406 cN.m	0.5-36 lbf.in		159	280	+/- 6%	2F	Blue
015600	Standard FH	6-406 cN.m	0.5-36 lbf.in		127	280	+/- 6%	2F	Blue
015605	Standard FH O/W	6-406 cN.m	0.5-36 lbf.in		127	280	+/- 6%	2F	Blue
015520	Standard SD	6-406 cN.m	0.5-36 lbf.in		159	280	+/- 6%	2F	Green
015525	Standard SD O/W	6-406 cN.m	0.5-36 lbf.in		159	280	+/- 6%	2F	Green
015620	Standard FH	6-406 cN.m	0.5-36 lbf.in		127	280	+/- 6%	2F	Green
015625	Standard FH O/W	6-406 cN.m	0.5-36 lbf.in		127	280	+/- 6%	2F	Green
015540	Standard SD	6-406 cN.m	0.5-36 lbf.in		159	280	+/- 6%	2F	Red
015545	Standard SD O/W	6-406 cN.m	0.5-36 lbf.in		159	280	+/- 6%	2F	Red
015640	Standard FH	6-406 cN.m	0.5-36 lbf.in		127	280	+/- 6%	2F	Red
015645	Standard FH O/W	6-406 cN.m	0.5-36 lbf.in		127	280	+/- 6%	2F	Red
015560	Standard SD	6-406 cN.m	0.5-36 lbf.in		159	280	+/- 6%	2F	Gold
015565	Standard SD O/W	6-406 cN.m	0.5-36 lbf.in		159	280	+/- 6%	2F	Gold
015660	Standard FH	6-406 cN.m	0.5-36 lbf.in		127	280	+/- 6%	2F	Gold
015665	Standard FH O/W	6-406 cN.m	0.5-36 lbf.in		127	280	+/- 6%	2F	Gold



Torqueleader offers a **Tool Presetting Service**... for more details please contact us on **+44 (0) 1483 894 476** to talk to one of our Sales Team



# Quickset Adjustable Torque Screwdrivers

## Torque range from 0.2 to 9 N.m

Calibrated scale tools using Slipping Technology to eliminate under and over tightening

### Industry Sectors

Maintenance & Repair



Like this tool, but need to be EPA Compliant... see pages 22-23 or visit [www.torqueleader.com](http://www.torqueleader.com)

### Slipping Mechanism

Incorrect tightening is impossible



Quickset 6 SD

Quickset 6 SH

### Key Benefits

- Quickset screwdrivers achieve accurate torque application by eliminating both under and over tightening using Torqueleader's proven slipping technology. This enables any user to deliver the correct torque with confidence regardless of task and operator skill level
- Fast and accurate to set, using the quick and clear to read micrometer setting scale
- A single tool can cover a broad variety of applications due to its wide torque range
- Long service life is provided through the durable design utilising hard wearing materials such as stainless steel and aluminum



Calibrate your Quickset Screwdriver... visit [www.torqueleader.com](http://www.torqueleader.com) for more details about our on site UKAS (United Kingdom Accreditation Service) Calibration Laboratory

## Models... Quickset (ISO & Imperial Scales)

All models available with either 1/4" Square Drive (SD) or 1/4" Female Hex (FH) Drive

Want to know how to use this tool?  
 Watch our video



Details of Accessories... see pages 65-66 or visit [www.torqueleader.com](http://www.torqueleader.com)



Order now... call our Sales Hotline +44 (0) 1483 894 476

Order Code	Model	← Calibrated Range →		Drive	k mm	g	Accuracy	ISO 6789 Class	Colour
		Range	للسلسلا						
016000	Quickset Minor Metric SD	20-120 cN.m	1 cN.m	1/4"	160	158	+/- 6%	2D	Black
016040	Quickset Minor Metric FH	20-120 cN.m	1 cN.m	1/4"	169	165	+/- 6%	2D	Black
016020	Quickset Minor Imp SD	20-120 ozf.in	1 ozf.in	1/4"	160	158	+/- 6%	2D	Black
016060	Quickset Minor Imp FH	20-120 ozf.in	1 ozf.in	1/4"	169	165	+/- 6%	2D	Black
016080	Quickset Minor lbf.in SD	2-12 lbf.in	0.1 lbf.in	1/4"	160	158	+/- 6%	2D	Grey
016070	Quickset Minor lbf.in FH	2-12 lbf.in	0.1 lbf.in	1/4"	169	165	+/- 6%	2D	Grey
016100*	Quickset 6 SD	1-6 N.m	0.1 N.m	1/4"	222	340	+/- 6%	2D	Red
016500*	Quickset 6 FH	1-6 N.m	0.1 N.m	1/4"	184	335	+/- 6%	2D	Red
016200*	Quickset 50 SD	5-50 lbf.in	1 lbf.in	1/2"	222	340	+/- 6%	2D	Red
016600*	Quickset 50 FH	5-50 lbf.in	1 lbf.in	1/2"	184	335	+/- 6%	2D	Red
016300*	Quickset 9 SD	4-9 N.m	0.1 N.m	1/2"	222	340	+/- 6%	2D	Green
016700*	Quickset 9 FH	4-9 N.m	0.1 N.m	1/2"	184	335	+/- 6%	2D	Green
016400*	Quickset 80 SD	40-80 lbf.in	1 lbf.in	1/2"	222	340	+/- 6%	2D	Green
016800*	Quickset 80 FH	40-80 lbf.in	1 lbf.in	1/2"	184	335	+/- 6%	2D	Green

\* Compatible with Lock On T-Bar (Order Code P29530)